



ASX ANNOUNCEMENT

Date: 13 June 2014

ASX: IPT

Number: 351/130614

FURTHER DRILL TARGETS AT COMMONWEALTH SOUTH PROSPECT AND POSSIBLE NEW MINERALISED TRENDS IDENTIFIED BY IP SURVEY, COMMONWEALTH PROJECT, NSW

Strong Induced Polarisation anomalies define large targets for disseminated sulphide mineralisation below previous mineralised drill intercepts at Commonwealth South: anomalies to be tested in up-coming drill programme

New IP anomalies define along-strike extension to the Silica Hill Prospect

New IP trend identified at depth, west of the Commonwealth Trend

Further large and strong induced polarisation anomalies that may be caused by extensive disseminated sulphide mineralisation have been identified in a ground geophysical survey at Impact Minerals Limited (ASX:IPT) 100% owned Commonwealth Project, 95 km north of Orange, NSW.

These new anomalies, which include direct drill targets at the Commonwealth South Prospect, have defined three sub-parallel trends in the IP data: the Commonwealth Trend, the Silica Hill Trend and the Western Trend, each of which is at least 300 m long (Figure 1). The drill targets are in addition to those recently identified at Main Shaft and Silica Hill (see announcement [4th June 2014](#)).

Drill targets at Commonwealth South

At the Commonwealth South Prospect, along the Commonwealth Trend, IP anomalies within 100 m of surface are in part coincident with, and thus consistent with, previously recognised disseminated sulphides that contain significant gold-silver-zinc-lead mineralisation (Figures 2 and 3).

For example, on survey line 9,700N (Figure 2) Hole CW20 has intersected a near-surface IP anomaly and returned mineralisation over a 30 m thick interval including:

6.9 m at 3.4 g/t gold, 72 g/t silver, 2.2% zinc and 1% lead from 30 m and

5.5 m at 3.8 g/t gold, 45 g/t silver, 0.8% zinc and 0.3% lead from 44 metres.

The mineralisation and IP anomaly are both open at depth and along strike and will be tested with a traverse of drill holes. The holes and IP anomalies are shown in Figure 3, a long section from Main Shaft to Commonwealth South that also shows previous drill intercepts for gold and silver.

In addition a stronger and larger IP anomaly that has not been drill tested occurs down dip of the mineralisation at Commonwealth South at a depth of about 200 m below surface (Figure 2 and 3).

Hole CM4, drilled between the shallower and deeper IP anomalies, identified a broad zone of modest mineralisation that returned 37 m at 0.2 g/t gold, 5.3 g/t silver, 0.2% zinc and 0.1% lead from 100 m depth (Figures 2 and 3). This intercept may indicate further mineralisation could occur below this drill hole, coincident with the deeper IP anomaly, which is at about the same depth as the IP anomaly recently identified below Main Shaft and will also be drill tested (Figure 3).




Figure 1. Geology of the Commonwealth area showing the location of the IP Survey Lines and soil geochemistry results (see announcement dated 12th May 2014).




Figure 2. Results of an Induced Polarisation Survey over the Commonwealth South Prospect showing the three IP Trends and soil geochemistry responses over the areas. The Western Trend lies beneath alluvial cover (see Figure 1 for location of survey line).




Figure 3. Long Section between Main Shaft and Commonwealth South Prospects showing the location of previous drill holes, significant gold and silver mineralisation and the IP anomalies.

The Silica Hill Trend and Western Trend

Two further IP trends have also been identified in the survey data (Figures 1 and 2).

The Silica Hill Trend contains possible extensions at depth to the strong IP anomaly recently identified at Silica Hill that is coincident with strong gold- and silver-in-soil anomalies (see announcements dated [4th June 2014](#) and [12th May 2014](#)). This trend has not been drilled.

The Western Trend, which is also undrilled, contains strong IP anomalies at depths of up to 200 m below surface. There has been no work in this area, which lies under thin alluvial cover that may have inhibited any surface response in soil geochemistry data (Figure 2).

Further interpretation of the IP data along the Silica Hill and Western Trends is in progress. However the direct association between significant high-grade mineralisation and IP anomalies along the Commonwealth Trend is encouraging for the discovery of further mineralisation along these two newly recognised trends.

All three trends are open to the south and the Commonwealth and Silica Hill Trends are open to the north as well. Further IP surveys will be required in these areas.

Next Steps

A drill programme to test the IP anomalies identified at Commonwealth South, Main Shaft and Silica Hill has been designed. The holes at Commonwealth South and Main Shaft are shown in Figure 3.


In addition a number of drill holes will be completed to verify previous drill intercepts and to allow the calculation of an Inferred Resource for the Commonwealth South to Main Shaft area.

The statutory approvals for the drill programme are due to be received in late June and drilling will commence as soon as practicable after that.

A further announcement will be made in due course to provide further details on the drill programme.

The Commonwealth Project lies 100 km north of the Cadia-Ridgeway porphyry-hosted deposits that contain 70 million ounces of gold and 12 million tonnes of copper within the highly prospective Lachlan Fold Belt, host to many major gold-silver-base metal mines.

Figure 4. Location of the Commonwealth Project and Location of Major Mines and Deposits in the Lachlan fold Belt of New South Wales.



ABOUT THE COMMONWEALTH PROJECT

The Commonwealth Mine, a high grade volcanogenic massive sulphide deposit (VMS), was discovered in 1900 and mined intermittently until the 1930's. Early production amounted to 470 oz of gold from 480 tons of oxide ore. A blast furnace was installed in 1905 and **6,476 t was mined at a grade of 6 g/t gold, 150 g/t silver, 2% copper, 15% zinc and 7% lead**. Operations were suspended in 1908 following flooding and there are no records of significant mining activity since.

The project has received little exploration attention in the past 25 years. Previous drilling was focused on 300 m of strike between the Commonwealth Mine and the Commonwealth South Prospect and only 66 drill holes for 3,695 m at an average depth of only 56 metres were completed (Figure 5).

Recent work by Impact (and Invictus) has included detailed re-logging of available diamond core that for the first time has applied a consistent geological framework to the rock types and alteration in the area. This work has been used to produce new maps and cross sections for the area. These are shown in Figures 5, 6, 7 and 8.

Impact's work has identified significant potential for both further high grade VMS deposits at depth and along strike from the Commonwealth Mine and importantly bulk tonnage lower grade disseminated gold and silver mineralisation that either was not recognised or was ignored by the early miners and previous explorers. In addition it is interpreted that there are at least two mineralised horizons in the rock sequence.

Exploratory underground drill holes completed in the 1980's discovered high grade mineralisation (remnant ore) which is still present at the Commonwealth Mine. Drill intercepts included:

**7 m at 5.3 g/t gold, 346 g/t silver, 9.2% zinc and 3.2% lead in CM85-1; and
3 m at 8 g/t gold, 158 g/t silver, 2.9% zinc and 0.8% lead in CM85-2.**

A long section with previous drill results for gold and silver shows that mineralisation between the Commonwealth Mine and the Commonwealth South Prospect is continuous and that two high grade shoots are present with values of more than 50 gram*metres gold equivalent (Figure 9).

In particular the long section and cross sections show high grade drill intercepts over robust widths that are open at depth and along strike and which confirm the potential for bulk tonnage mining at Commonwealth. These intercepts include:

At the Commonwealth Mine (Figures 4, 5 and 8):

**9.8 m at 8.4 g/t gold and 357 g/t silver from 54.2 m in CW29;
4.7 m at 5.5 g/t gold and 253 g/t silver from 54.3 m in CW30; and
17 m at 3.5 g/t gold and 206 g/t silver from 41 m in EMC06.**

At Commonwealth South (Figures 4, 6 and 7):

**30 m at 6 g/t gold and 17 g/t silver from 24 m including 2 m at 77.3 g/t gold in PHC4;
26 m at 2.5 g/t gold and 20 g/t silver from 32 m in PHC9; and
6.9 m at 3.4 g/t gold, 72 g/t silver, 2.2% zinc and 1% lead from 30 m and
5.5 m at 3.8 g/t gold, 45 g/t silver, 0.8% zinc and 0.3% lead from 44 m in CW20.**



ASX Code: **IPT**

Dr Michael G Jones
Managing Director

The review of exploration activities and results contained in this report is based on information compiled by Dr Mike Jones, a Member of the Australian Institute of Geoscientists. He is a director of the company and works for Impact Minerals Limited. He has sufficient experience which is relevant to the style of mineralisation and types of deposits under consideration and to the activity which he is undertaking to qualify as a Competent Person as defined in the 2012 edition of the Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves (the JORC Code). Mike Jones has consented to the inclusion in the report of the matters based on his information in the form and context in which it appears.




Figure 5. Geology and Mineralisation of the Commonwealth Mine to Commonwealth South area.




Figure 6. Cross section 1 (Figure 5) showing the geology and key drill results beneath the main shaft at Commonwealth.




Figure 7. Cross Section 2 (Figure 5) showing the geology and key drill results in the centre of the Commonwealth South Prospect.




Figure 8. Cross Section 3 (Figure 5) showing the geology and key drill results at the southern end of the Commonwealth South Prospect.




Figure 9. Long section between Commonwealth Mine and Commonwealth South showing gold-equivalent grade times thickness contours (in gram*metres) and key drill results.



ASX Code: **IPT**

Company Information

Impact Minerals Limited

ACN 119 062 261

ABN 51 119 062 261

Directors

Peter Unsworth Non-Executive Chairman

Michael Jones Managing Director

Paul Ingram Non-Executive Director

Markus Elsasser Non-Executive Director

Company Secretary

James Cooper-Jones

Registered & Administrative Office

309 Newcastle Street
Northbridge Western Australia 6003

Telephone: +61 (8) 6454 6666

Facsimile: +61 (8) 6454 6667

Email: info@impactminerals.com.au

Website: www.impactminerals.com.au

Share Registry

Computershare Investor Services Pty Ltd

GPO Box D182

Perth WA 6840

Australia

Telephone: +61 (8) 9323 2000

Facsimile: +61 (8) 9323 2033

Email:

perth.services@computershare.com.au

Australian Stock Exchange Listing

Shares IPT

Major shareholders as at 1.3.14

Bunnenberg Family 31%

Directors 11%

Top 20 58%

Top 50 69%

Capital Structure as at 1.3.14

Ordinary Shares on Issue 487,063,284

Total Listed Options 8,000,000

Total Unlisted Options 34,300,000

An ASX listed Australian company focused on nickel- copper-PGE and uranium exploration

ABN 52 119 062 261



ASX Code: IPT



APPENDIX 1 - SECTION 1 SAMPLING TECHNIQUES AND DATA

Criteria	JORC Code explanation	Commentary
Sampling techniques	<i>Nature and quality of sampling (e.g. cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.</i>	Random rock samples were taken at surface which represented favourable geology and alteration to known mineralisation in the region. Samples are variably weathered.
	<i>Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used</i>	Representative samples at each sample site weigh between 0.8 and 1.2 kg. Sample site area was chosen due to historic rock and soil assay results and the EM survey conducted on the Commonwealth Project. Historic rock sample methods are unknown but are considered immaterial.
	<i>Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (e.g. 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (e.g. submarine nodules) may warrant disclosure of detailed information</i>	Rock samples were sent to SGS Perth where they were crushed, dried and pulverised (total prep) to produce a 25-30 g sub-samples for analysis initially by Aqua Regia digest with ICP-MS finish for base metals then by four acid digest with an ICP/AES finish for ore grade base metal samples and lead collection fire assay with AAS finish for gold. Historical diamond and RC samples were sent to Fox Anamet, Brookvale NSW where gold was determined by fire assay, base metals by DCP and AAS methods. Weathered samples contained gossanous sulphide material and fresh samples containing visible pyrite, galena, sphalerite and chalcopyrite.
Drilling techniques	<i>Drill type (e.g. core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (e.g. core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).</i>	Historical diamond drilling accounts for 76 % of the drilling and comprises NQ sized core. Historical RC drilling accounts for 24% of the drilling and comprises 6.75 inch/17.1 cm sized core. Historic core is not oriented downhole but this is not material for the results reported here.
Drill sample recovery	<i>Method of recording and assessing core and chip sample recoveries and results assessed</i>	Historical diamond core recoveries for selected holes are logged and recorded. Overall recoveries have not yet been calculated but are estimated to be approximately >95% for the Commonwealth Project. No significant core loss or sample recovery problems are observed in the drill core or historic reports.
	<i>Measures taken to maximise sample recovery and ensure representative nature of the samples</i>	Depths were checked against the depth given on the core blocks and rod counts are routinely carried out by the drillers. RC samples were visually checked for recovery, moisture and contamination.
	<i>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</i>	No sample bias has been established. However there is an indication that wet RC samples may give lower gold grades due to loss of fine gold.
Logging	<i>Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</i>	For historical diamond core information on structure type, dip, dip direction, texture, shape and fill material has been recorded in the logs. Angles are measured to core axis since core orientation was not done. RQD data has been recorded on selected historic diamond holes.

An ASX listed Australian company focused on uranium and copper-nickel-PGE exploration.



ASX Code: **IPT**



Criteria	JORC Code explanation	Commentary
	<i>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.</i>	Logging of historic diamond core and RC samples recorded lithology, mineralogy, mineralisation, structural (DDH only), weathering, colour and other features of the samples.
	<i>The total length and percentage of the relevant intersections logged</i>	All historic diamond drillholes were logged in full.
Sub-sampling techniques and sample preparation	<i>If core, whether cut or sawn and whether quarter, half or all core taken.</i>	All NQ core samples were samples by half core and selected intervals of quarter core were selected for check assays.
	<i>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</i>	RC samples were split using a riffle splitter.
	<i>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</i>	The sample preparation of rock chips by Impact at Commonwealth follows industry best practice in sample preparation involving oven drying, coarse crushing down to ~10 mm followed by pulverisation of the entire sample (total prep) to a grind size of 85% passing 75 micron.
	<i>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</i>	Laboratory QC procedures for rock sample assays involve the use of internal certified reference material as assay standards, along with blanks, duplicates and replicates. The QC procedure for historical diamond and RC samples is unknown but considered immaterial.
	<i>Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.</i>	Sample duplicates from the historical drilling were taken from selected intervals and compared to the original assay. Quarter core was taken for diamond samples and riffle resplits for RC samples.
	<i>Whether sample sizes are appropriate to the grain size of the material being sampled.</i>	The samples sizes at Commonwealth are considered appropriate since gold has been identified as predominantly fine-grained by thin section analysis which would indicate the nugget effect is minimal.
Quality of assay data and laboratory tests	<i>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</i>	An industry standard fire assay technique for rock chips using lead collection with an Atomic Absorption Spectrometry (AAS) finish was used for gold. The quality of historical drill sample assays is unknown, however this is considered immaterial at this stage of exploration.
	<i>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</i>	No geophysical tools were used to determine material element concentrations.
	<i>Nature of quality control procedures adopted (e.g. standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (i.e. lack of bias) and precision have been established.</i>	For the rock chips, quality control procedures for assays were followed via internal SGS protocols. Accuracy and precision are within acceptable limits. The quality control of historical drill sample assays is unknown, however this is considered immaterial at this stage of exploration.
Verification of sampling and assaying	<i>The verification of significant intersections by either independent or alternative company personnel.</i>	Significant intersections from historic drilling have not been verified by independent or alternative companies. This is not required at this stage of exploration.

An ASX listed Australian company focused on uranium and copper-nickel-PGE exploration.



ASX Code: **IPT**



Criteria	JORC Code explanation	Commentary
	<i>The use of twinned holes.</i>	Twin historical diamond versus RC hole was drilled at Commonwealth South.
	<i>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</i>	Primary assay data for rock chips has been entered into standard Excel templates for plotting on Mapinfo. All historical drill data has been entered digitally by previous explorers and verified internally by Impact.
	<i>Discuss any adjustment to assay data.</i>	Any identified historic data entry errors have been adjusted by Impact and recorded in the comments.
Location of data points	<i>Accuracy and quality of surveys used to locate drillholes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</i>	Recent drill holes have been located by DGPS. Historical drill holes and mine shafts have been verified by the DGPS.
	<i>Specification of the grid system used.</i>	The grid system for Commonwealth is MGA_GDA94, Zone 55.
	<i>Quality and adequacy of topographic control.</i>	Standard government topographic maps have been used for topographic validation. The DGPS is considered sufficiently accurate for elevation data.
Data spacing and distribution	<i>Data spacing for reporting of Exploration Results.</i>	Drill spacing of historical drill holes ranges between 10 and 30 m which is considered adequate for Exploration Results.
	<i>Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</i>	Drill spacing of historical drill holes ranges between 10 and 30 m and may be considered adequate for Mineral Resource and Ore reserve estimation procedures. However estimations of grade and tonnes have not yet been made.
	<i>Whether sample compositing has been applied.</i>	Sample compositing has been applied for quoting drill composite results only.
Orientation of data in relation to geological structure	<i>Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.</i>	Historical drilling is oriented sub-perpendicular to the mineralised trend and stratigraphic contacts as determined by field data and cross section interpretation.
	<i>If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</i>	No significant sample bias has been identified from historical drilling due to the optimum drill orientation described above. Where present, sample bias will be reported.
Sample security	<i>The measures taken to ensure sample security.</i>	For rock samples, chain of custody is managed by Impact Minerals Ltd. Samples for Commonwealth are delivered by Impact Minerals Ltd personnel to SGS Perth for prep and assay. Whilst in storage, they are kept in a locked yard. Tracking sheets have been set up to track the progress of batches of samples. Security of historic drill samples is unknown however is considered immaterial.
Audits or reviews	<i>The results of any audits or reviews of sampling techniques and data.</i>	At this stage of exploration a review of the sampling techniques and data by an external party is not warranted. An internal review of the sampling techniques and data will be completed in due course.

An ASX listed Australian company focused on uranium and copper-nickel-PGE exploration.



ASX Code: **IPT**



SECTION 2 REPORTING OF EXPLORATION RESULTS

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.	The Commonwealth Project currently comprises 1 exploration licences covering 8 km ² . The tenement is held 100% by Endeavour Minerals Pty Ltd which has been acquired by Impact Minerals Limited. No aboriginal sites or places have been declared or recorded over the licence area. There are no national parks over the license area.
	The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.	The tenement is in good standing with no known impediments.
Exploration done by other parties	Acknowledgment and appraisal of exploration by other parties.	A total of 66 drillholes have been completed over 300 m strike between the Commonwealth main shaft and Commonwealth South by previous explorers to an average depth of 53 m.
Geology	Deposit type, geological setting and style of mineralisation.	The Commonwealth and Commonwealth South deposits are considered gold-rich volcanic hosted massive sulphide (VMS) deposits that occur at and below the contact with a porphyritic rhyolite and overlying volcanic sedimentary rocks.
Drill hole Information	<p>A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes:</p> <ul style="list-style-type: none"> • easting and northing of the drill hole collar • elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar • dip and azimuth of the hole • down hole length and interception depth • hole length. 	Further details are not material for this early stage of exploration. Information on the historic drill holes is currently being compiled.
Data aggregation methods	In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (e.g. cutting of high grades) and cut-off grades are usually Material and should be stated.	All reported assays have been length weighted. No top cuts have been applied. A nominal cut-off of approximately 0.5 g/t Au has been applied.
	Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.	High grade massive sulphide intervals internal to broader zones of disseminated sulphide mineralisation are reported as included intervals.
	The assumptions used for any reporting of metal equivalent values should be clearly stated.	Gold equivalent values have been used in the long section. Metal prices used for the gold equivalent were \$1,650 for gold and \$30 for silver. Given the high grade results, it is assumed that very high recoveries will be achieved. However no metallurgical studies have been completed to verify this. Such studies will be done as and when appropriate.

An ASX listed Australian company focused on uranium and copper-nickel-PGE exploration.



ASX Code: **IPT**



Criteria	JORC Code explanation	Commentary
Relationship between mineralisation widths and intercept lengths	<p>These relationships are particularly important in the reporting of Exploration Results.</p> <p>If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported.</p> <p>If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (e.g. 'down hole length, true width not known').</p>	Historical drill holes to date have been sub-perpendicular to the mineralised trend and stratigraphy so intervals are close to true width or otherwise stated.
Diagrams	<p>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.</p>	Refer to Figures in body of text.
Balanced reporting	<p>Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</p>	All results reported are representative
Other substantive exploration data	<p>Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.</p>	Assessment of other substantive exploration data is not yet complete however considered immaterial at this stage.
Further work	<p>The nature and scale of planned further work (e.g. tests for lateral extensions or depth extensions or large-scale step-out drilling).</p> <p>Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive</p>	Follow up work programmes will be subject to interpretation of recent and historic results which is ongoing.

An ASX listed Australian company focused on uranium and copper-nickel-PGE exploration.